

COMBINATORI A STELLA

FDT/2000S - 2000S-H - 4000S - 6000S - 10000S



VERSIONE SPECIALE PER SPAZIATURA LIMITATA FRA I CANALI

Mod.	Freq. Mhz	Imped	SWR	Att.	Conn. In/out	Power	Isol.	Dimens. Cm	Peso
FDT/2000S	87.5-108	50 ohm	< 1.2:1	<0.6 db	N-7/16	2x800W	>30db	41x40x130	32Kg
FDT/2000S-H	87.5-108	50 ohm	< 1.2:1	<0.6 db	7/16-7/8	2x1.2KW	>30db	41x40x130	34Kg
FDT/4000S	87.5-108	50 ohm	< 1.2:1	<0.5 db	7/16-7/8	2x2KW	>30db	41x60x130	58Kg
FDT/6000S	87.5-108	50 ohm	< 1.2:1	<0.5 db	7/8-1+5/8	2x3KW	>30db	41x60x130	60Kg
FDT/10000S	87.5-108	50 ohm	< 1.2:1	<0.5 db	7/8-1+5/8	2x5KW	>30db	70x73x130	90Kg

NOTE:

Sono composti da due filtri in cavità **Tripla** e dalle opportune linee rigide; hanno tutti gli ingressi selettivi e all'atto dell'ordine occorre specificare le frequenze di utilizzo. Tipicamente la distanza minima fra i canali deve essere non inferiore ad almeno 1.5Mhz.

CURVE DI ATTENUAZIONE E SWR

