

TX station: 12xAky3  
Gain solid integration : enabled

Site Name: Labelitaly

### General data of Antenna System

TX station	12xAky3
Site Name	Labelitaly
System of coordinates	Geographic
Longitude	00°00'00.000"
Latitude	00°00'00.000"
Ground level a.s.l. (m)	100.0
Antenna system height (m)	50.0
Transmitter power(Watt)	1000.000
Carrier wave frequency (MHz)	98.000
Antenna system central frequency (MHz)	98.000
Antenna base diagrams type 1	LABEL ITALY-AKY_3 YAGI FM WB 3 ELEM.
Antenna base diagrams type 2	-
Polarization (H/V/C/X)	V
Transmitting cable attenuation (dB)	0.0
Additional attenuations(dB)	0.0
Base diagrams sectors (T = All, F = Front)	T
Velocity factor of cables to Antennas (0÷1)	0.88
Coordinate System(C = cartesian, P = polar)	P
Mast side / diameter(cm):	10.0
Mast cross section (T/Q/C)	C
Structure rotation w.r.t. North (°)	0.0
Mast rotation w.r.t. North (°)	0.0

### Information about antennas used in the System

	<i>Antenna type 1</i>
Manufacturer	LABEL ITALY
Antenna model	AKY_3 YAGI FM WB 3
Band start(MHz)	88
Band stop(MHz)	108
diagrams Frequency(MHz)	98
Polariz (H,V,C,X)	V
Vertical dist (cm)	260
Height (cm)	180
Width (cm)	6
Thickness (cm)	125
Weight (Kg)	13
Maximum power (KW)	3
Gain (dBd)	5.22
North E.C. (cm)	0
East E.C. (cm)	0
Return loss (dB)	20
R.C.Phase (°)	0

TX station: 12xAky3  
Frequency: 98.00 MHz  
Gain solid integration : enabled

Site Name: Labelitaly


Geometr. and electrical data of Antenna System

	<i>Power</i> (%)	<i>Tilt</i> (°)	<i>Az.</i> (°/N)	<i>Phase</i> (°)	<i>V dist.</i> (m)	<i>Scr-d</i> (cm)	<i>Scr-Az</i> (°/N)	<i>Rot.</i> (1÷4)	<i>Type</i> (1÷2)	<i>L cables</i> (cm)	<i>Car. phase</i> (°)
1	10.000	0	0	0 +0.0	11.70	0.0	0.0	1	1	0.0	0.0
2	10.000	0	0	0 +0.0	9.10	0.0	0.0	1	1	0.0	0.0
3	10.000	0	0	0 +0.0	6.50	0.0	0.0	1	1	0.0	0.0
4	10.000	0	0	0 +0.0	3.90	0.0	0.0	1	1	0.0	0.0
5	10.000	0	0	0 +0.0	1.30	0.0	0.0	1	1	0.0	0.0
6	10.000	0	0	0 +0.0	-1.30	0.0	0.0	1	1	0.0	0.0
7	10.000	0	0	0 +0.0	-3.90	0.0	0.0	1	1	0.0	0.0
8	10.000	0	0	0 +0.0	-6.50	0.0	0.0	1	1	0.0	0.0
9	10.000	0	0	0 +0.0	-9.10	0.0	0.0	1	1	0.0	0.0
10	10.000	0	0	0 +0.0	-11.70	0.0	0.0	1	1	0.0	0.0

TX station: 12xAky3  
Frequency: 98.00 MHz  
Gain solid integration : enabled

Site Name: Labelitaly

Plan of antenna system



Side of antenna system



TX station: 12xAky3  
Frequency: 98.00 MHz  
Gain solid integration : enabled

Site Name: Labelitaly

Antennas arrays data

A. Antennas array azimuth (°/N)	0
B. Number of antennas	10
C. Nominal power supply (W)	1000.00
D. Losses (addit. + cables) (dB)	0.0
E. Effective power supply (W)	1000.00
F. Theor. maximum gain (dBd)	14.15
G. Distribution losses (dB)	0.00
H. Nominal max gain [F - G] (dBd)	14.15
I. Compensation losses (dB)	0.00
J. Effec. max gain [H - I] (dBd)	14.15
K. Effec. max gain (times)	26.01
L. Effec. max power [E * K] (KW)	26.0084
M. Max power depr. angle (°)	0.0
N. Max power az. angle (°)	0


Diagram in dBK calculated at horizon

Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK
0	14.2	90	8.1	180	0.8	270	8.1
10	14.1	100	6.4	190	0.8	280	9.6
20	14.0	110	4.8	200	0.8	290	10.8
30	13.7	120	3.3	210	1.0	300	11.9
40	13.3	130	2.3	220	1.5	310	12.7
50	12.7	140	1.5	230	2.3	320	13.3
60	11.9	150	1.0	240	3.3	330	13.7
70	10.8	160	0.8	250	4.8	340	14.0
80	9.6	170	0.8	260	6.4	350	14.1

TX station: 12xAky3  
Frequency: 98.00 MHz  
Gain solid integration : enabled

Site Name: Labelitaly

Horizontal diagram at 0.0° depres. (Total Antenna)




0.0° depres. (Total Antenna), Gain (dBd): 14.15 ERP T.Max(KW): 26.0084 ERP E.Max(KW): 26.0084

TX station: 12xAky3  
Frequency: 98.00 MHz  
Gain solid integration : enabled

Site Name: Labelitaly

Vertical diagram at an azimuth of 0.0° degrees



0.0° Az. (Total Antenna), Gain (dBd): 14.15

ERP T.Max(KW): 26.0084    ERP E.Max(KW): 26.0084