

TX station: 8xBkk2-h-omni
Gain solid integration : disabled

Site Name: Labelitaly

General data of Antenna System

TX station	8xBkk2-h-omni
Site Name	Labelitaly
System of coordinates	Geographic
Longitude	00°00'00.000"
Latitude	00°00'00.000"
Ground level a.s.l. (m)	100.0
Antenna system height (m)	50.0
Transmitter power(Watt)	1000.000
Carrier wave frequency (MHz)	200.000
Antenna system central frequency (MHz)	200.000
Antenna base diagrams type 1	LABEL ITALY-BKK_2V PANEL VHF WB
Antenna base diagrams type 2	-
Polarization (H/V/C/X)	H
Transmitting cable attenuation (dB)	0.0
Additional attenuations(dB)	0.0
Base diagrams sectors (T = All, F = Front)	T
Velocity factor of cables to Antennas (0÷1)	0.88
Coordinate System(C = cartesian, P = polar)	P
Mast side / diameter(cm):	100.0
Mast cross section (T/Q/C)	Q
Structure rotation w.r.t. North (°)	0.0
Mast rotation w.r.t. North (°)	0.0

Information about antennas used in the System

	<i>Antenna type 1</i>
Manufacturer	LABEL ITALY
Antenna model	BKK_2V PANEL VHF WB
Band start(MHz)	174
Band stop(MHz)	225
diagrams Frequency(MHz)	200
Polariz (H,V,C,X)	V
Vertical dist (cm)	150
Height (cm)	87
Width (cm)	125
Thickness (cm)	40
Weight (Kg)	25
Maximum power (KW)	2
Gain (dBd)	7.5
North E.C. (cm)	0
East E.C. (cm)	0
Return loss (dB)	24
R.C.Phase (°)	0


TX station: 8xBkk2-h-omni
Frequency: 200.00 MHz
Gain solid integration : disabled

Site Name: Labelitaly

Geometr. and electrical data of Antenna System


	<i>Power</i> (%)	<i>Tilt</i> (°)	<i>Az.</i> (°/N)	<i>Phase</i> (°)		<i>V dist.</i> (m)	<i>Scr-d</i> (cm)	<i>Scr-Az</i> (°/N)	<i>Rot.</i> (1÷4)	<i>Type</i> (1÷2)	<i>L cables</i> (cm)	<i>Car. phase</i> (°)
1	12.500	0	0	0	+0.0	1.50	60.0	0.0	2	1	0.0	0.0
2	12.500	0	0	0	+0.0	0.00	60.0	0.0	2	1	0.0	0.0
3	12.500	0	90	0	+0.0	1.50	60.0	90.0	2	1	0.0	0.0
4	12.500	0	90	0	+0.0	0.00	60.0	90.0	2	1	0.0	0.0
5	12.500	0	180	0	+0.0	1.50	60.0	180.0	2	1	0.0	0.0
6	12.500	0	180	0	+0.0	0.00	60.0	180.0	2	1	0.0	0.0
7	12.500	0	270	0	+0.0	1.50	60.0	270.0	2	1	0.0	0.0
8	12.500	0	270	0	+0.0	0.00	60.0	270.0	2	1	0.0	0.0

Plan of antenna system



Side of antenna system

* = rotated antenna



Antennas arrays data

A. Antennas array azimuth (°/N)	0	90	180	270
B. Number of antennas	2	2	2	2
C. Nominal power supply (W)	250.00	250.00	250.00	250.00
D. Losses (addit. + cables) (dB)	0.0	0.0	0.0	0.0
E. Effective power supply (W)	250.00	250.00	250.00	250.00
F. Theor. maximum gain (dBd)	10.51	10.51	10.51	10.51
G. Distribution losses (dB)	0.00	0.00	0.00	0.00
H. Nominal max gain [F - G] (dBd)	10.51	10.51	10.51	10.51
I. Compensation losses (dB)	0.00	0.00	0.00	0.00
J. Effec. max gain [H - I] (dBd)	10.51	10.51	10.51	10.51
K. Effec. max gain (times)	11.25	11.25	11.25	11.25
L. Effec. max power [E * K] (KW)	2.8117	2.8117	2.8117	2.8117
M. Max power depr. angle (°)	0.0	0.0	0.0	0.0
N. Max power az. angle (°)	0	90	180	270


Diagram in dBK calculated at horizon

Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK
0	4.5	90	4.5	180	4.5	270	4.5
10	3.4	100	3.4	190	3.4	280	3.4
20	2.8	110	2.8	200	2.8	290	2.8
30	3.4	120	3.4	210	3.4	300	3.4
40	4.3	130	4.3	220	4.3	310	4.3
50	4.3	140	4.3	230	4.3	320	4.3
60	3.4	150	3.4	240	3.4	330	3.4
70	2.8	160	2.8	250	2.8	340	2.8
80	3.4	170	3.4	260	3.4	350	3.4

TX station: 8xBkk2-h-omni
 Frequency: 200.00 MHz
 Gain solid integration : disabled

Site Name: Labelitaly

Horizontal diagram at 0.0° depres. (Total Antenna)



0.0° depres. (Total Antenna), Gain (dBd): 4.5 ERP T.Max(KW): 2.8179 ERP E.Max(KW): 2.8179


TX station: 8xBkk2-h-omni

Frequency: 200.00 MHz

Gain solid integration : disabled

Site Name: Labelitaly

Vertical diagram at an azimuth of 0.0° degrees



0.0° Az. (Total Antenna), Gain (dBd): 4.5

ERP T.Max(KW): 2.8179 ERP E.Max(KW): 2.8179