

General data of Antenna System

TX station	12xAkk2-3dir
Site Name	Labelitaly
System of coordinates	Geographic
Longitude	00°00'00.000"
Latitude	00°00'00.000"
Ground level a.s.l. (m)	100.0
Antenna system height (m)	50.0
Transmitter power(Watt)	1000.000
Carrier wave frequency (MHz)	98.000
Antenna system central frequency (MHz)	98.000
Antenna base diagrams type 1	LABEL ITALY-AKK_2V PANEL W.B. FM vertical pol.
Antenna base diagrams type 2	-
Polarization (H/V/C/X)	V
Transmitting cable attenuation (dB)	0.0
Additional attenuations(dB)	0.0
Base diagrams sectors (T = All, F = Front)	T
Velocity factor of cables to Antennas (0÷1)	0.88
Coordinate System(C = cartesian, P = polar)	P
Mast side / diameter(cm):	200.0
Mast cross section (T/Q/C)	Q
Structure rotation w.r.t. North (°)	0.0
Mast rotation w.r.t. North (°)	0.0

Information about antennas used in the System

	<i>Antenna type 1</i>
Manufacturer	LABEL ITALY
Antenna model	AKK_2V PANEL W.B. F
Band start(MHz)	88
Band stop(MHz)	105
diagrams Frequency(MHz)	98
Polariz (H,V,C,X)	V
Vertical dist (cm)	310
Height (cm)	174
Width (cm)	248
Thickness (cm)	80
Weight (Kg)	45
Maximum power (KW)	5
Gain (dBd)	8.1
North E.C. (cm)	0
East E.C. (cm)	0
Return loss (dB)	0
R.C.Phase (°)	0

TX station: 12xAkk2-3dir  
Frequency: 98.00 MHz  
Gain solid integration : disabled

Site Name: Labelitaly


Geometr. and electrical data of Antenna System

	<i>Power</i> (%)	<i>Tilt</i> (°)	<i>Az.</i> (°/N)	<i>Phase</i> (°)		<i>V dist.</i> (m)	<i>Scr-d</i> (cm)	<i>Scr-Az</i> (°/N)	<i>Rot.</i> (1÷4)	<i>Type</i> (1÷2)	<i>L cables</i> (cm)	<i>Car. phase</i> (°)
1	8.333	0	0	0	+0.0	4.20	160.0	0.0	1	1	0.0	0.0
2	8.333	0	0	0	+0.0	1.40	160.0	0.0	1	1	0.0	0.0
3	8.333	0	0	0	+0.0	-1.40	160.0	0.0	1	1	0.0	0.0
4	8.333	0	0	0	+0.0	-4.20	160.0	0.0	1	1	0.0	0.0
5	8.333	0	90	0	+0.0	4.20	170.0	90.0	1	1	0.0	0.0
6	8.333	0	90	0	+0.0	1.40	170.0	90.0	1	1	0.0	0.0
7	8.333	0	90	0	+0.0	-1.40	170.0	90.0	1	1	0.0	0.0
8	8.333	0	90	0	+0.0	-4.20	170.0	90.0	1	1	0.0	0.0
9	8.333	0	270	0	+0.0	4.20	170.0	270.0	1	1	0.0	0.0
10	8.333	0	270	0	+0.0	1.40	170.0	270.0	1	1	0.0	0.0
11	8.333	0	270	0	+0.0	-1.40	170.0	270.0	1	1	0.0	0.0
12	8.333	0	270	0	+0.0	-4.20	170.0	270.0	1	1	0.0	0.0


TX station: 12xAkk2-3dir  
Frequency: 98.00 MHz  
Gain solid integration : disabled

Site Name: Labelitaly

Plan of antenna system



Side of antenna system



Antennas arrays data

A. Antennas array azimuth (°/N)	0	90	270
B. Number of antennas	4	4	4
C. Nominal power supply (W)	333.33	333.33	333.33
D. Losses (addit. + cables) (dB)	0.0	0.0	0.0
E. Effective power supply (W)	333.33	333.33	333.33
F. Theor. maximum gain (dBd)	14.12	14.12	14.12
G. Distribution losses (dB)	0.00	0.00	0.00
H. Nominal max gain [F - G] (dBd)	14.12	14.12	14.12
I. Compensation losses (dB)	0.00	0.00	0.00
J. Effec. max gain [H - I] (dBd)	14.12	14.12	14.12
K. Effec. max gain (times)	25.83	25.83	25.83
L. Effec. max power [E * K] (KW)	8.6087	8.6087	8.6087
M. Max power depr. angle (°)	0.0	0.0	0.0
N. Max power az. angle (°)	358	88	268


Diagram in dBK calculated at horizon

Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK
0	7.5	90	8.7	180	-3.9	270	8.7
10	7.6	100	8.4	190	-5.1	280	8.3
20	7.6	110	7.7	200	-10.2	290	7.0
30	7.9	120	6.3	210	-5.7	300	6.7
40	8.0	130	4.0	220	1.3	310	7.6
50	7.6	140	1.3	230	4.0	320	8.0
60	6.7	150	-5.7	240	6.3	330	7.9
70	7.0	160	-10.2	250	7.7	340	7.6
80	8.3	170	-5.1	260	8.4	350	7.6

TX station: 12xAkk2-3dir  
Frequency: 98.00 MHz  
Gain solid integration : disabled

Site Name: Labelitaly

Horizontal diagram at 0.0° depres. (Total Antenna)




0.0° depres. (Total Antenna), Gain (dBd): 8.66 ERP T.Max(KW): 7.3531 ERP E.Max(KW): 7.3531

TX station: 12xAkk2-3dir  
Frequency: 98.00 MHz  
Gain solid integration : disabled

Site Name: Labelitaly

Vertical diagram at an azimuth of 0.0° degrees



0.0° Az. (Total Antenna), Gain (dBd): 7.51

ERP T.Max(KW): 5.6403    ERP E.Max(KW): 5.6403